



Client:	
Order #:	
Project:	
Type:	

DESCRIPTION

The REVT series Vapor Tight fixture withstands rugged environments and is available in 4-foot and 8-foot lengths. The fixture housing is made of clean and pure PC material with excellent stability and durability, and a stainless steel clip for easy installation. With the ability to switch lumens and adjust color temperature in one fixture, greatly reducing SKUs. Emergency Battery Back Up and sensor options are available. The REVT series vapor tight is ideal solutions for outdoor venues, canopies and locker rooms.

FEATURES

- Closed housing is sealed against moisture and environmental contaminants.
- Stainless steel clamp design, convenient assembly and separation of lamp body.
- 4 feet and 8 feet are available.
- Up to 90W output 12800 lumens.
- Adjustable lumen output with three lumen gears LV1, LV2, LV3.
- Switchable color temperature 3500K/4000K/5000K.

PERFORMANCE DATA

CRI

80+

CCT

3500K, 4000K, 5000K

Projected Lifetime

>100,000 Hours (L70)

Dimming

0-10V Dimming Standard,
10% down to 100%

Operating Temperature

-30°C to 50°C Ambient

Warranty

5 year Standard
10 year Optional

ORDERING INFORMATION

REVT / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____
SERIES SIZE WATTAGE CCT VOLTAGE DRIVER FEATURES FINISH CONTROLS EMERG. BATT. WARRANTY

FIXTURE SERIES	
REVT	Revo LED Vapor Tight
SIZE	
4	4 FT Nominal Length
8	8 FT Nominal Length
WATTAGE*	
45WS	34W, 38W, 45W Select. (4 FT)
90WS	65W, 75W, 90W Select. (8FT)



CCT	
CS	80+ CRI, 35K, 40K, 50K CCT Select.
VOLTAGE	
UNV	Universal 120-277VAC
DRIVER FEATURES	
10V	0-10V Dimming
12A	12V Aux Power & 0-10V Dimming
FINISH	
WH	White Finish

CONTROLS	
MPW	Motion PIR Occ. Plug'n'Play, Wet Loc.
MEW	Motion PIR Occ. Line Voltage, End Mount, Wet Loc.
MWPEW	Motion Sensor, Microwave Occ., Plug'n'Play, Aux 12 VDC, End Mnt. Wet Loc.
MWEW	Motion Sensor, Microwave Occ., Line Voltage, End Mount Wet Loc.
EMERGENCY BATT. BACKUP	
EM8	8 Watt (900 lm) 90 Min. Emerg. Batt.
EM15	15 Watt (1500 lm) 90 Min. Emerg. Batt.
WARRANTY	
-	5 Year Warranty (Standard)
10Y	10 Year Warranty
10YL	10 Year Warranty with Labor

DIMENSION



unit: mm/inch

45WS



Net Weight:
50W: 2.75kg(6.06lbs)
90W: 5.9kg(13lbs)

90WS



PERFORMANCE DATA







REVT 45WS 4FT

SETTING	SYSTEM WATTS	3500K		4000K		5000K	
		LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)
LV1	50W	6700lm	134 lm/W	7100lm	142 lm/W	6900lm	138 lm/W
LV2	35W	4780lm	137 lm/W	5100lm	146 lm/W	4900lm	140 lm/W
LV3	25W	3500lm	140 lm/W	3800lm	152 lm/W	3560lm	142 lm/W

REVT 90WS 8FT

SETTING	SYSTEM WATTS	3500K		4000K		5000K	
		LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)
LV1	90W	12200lm	136 lm/W	12800lm	142 lm/W	12500lm	139 lm/W
LV2	75W	10300lm	137 lm/W	10800lm	144 lm/W	10500lm	140 lm/W
LV3	60W	8300lm	138 lm/W	8800lm	147 lm/W	8500lm	142 lm/W

ACCESSORIES (Optional)

 <p>Mounting Bracket (Default)</p>	 <p>Emergency Battery 8W 900lm 90min (Sold separately)</p>	 <p>Microwave Sensor NO.: HD027VCR Description: 12VDC input (Sold separately)</p>
 <p>Chain Description: 30cm long (Default)</p>	 <p>Hardware bag (Default)</p>	 <p>Aircraft Cable Description: 3m long (Sold separately)</p>