



Client:	
Order #:	
Project:	
Type:	

DESCRIPTION

The VSW LED fixture combines a classic wrap look and feel with updated modern LED technology, making it a versatile and robust lighting solution. Its sleek design and advanced technology make it ideal for a variety of applications, including industrial, commercial, and institutional settings. The VSW fixture ensures reliable and efficient lighting, enhancing any space with its superior performance.

FEATURES

- Provides high-efficiency lighting at 150 LPW with superior lumen output.
- Designed for versatile applications, suitable for both indoor and outdoor use.
- Features a sleek and modern design that enhances any space.
- Offers multiple mounting options for flexible installation.
- Equipped with advanced LED technology for long-lasting performance.
- Ensures uniform light distribution with minimal glare.
- Available in various color temperatures to meet different lighting needs.
- Energy-efficient, reducing operational costs over time.

CONSTRUCTION & ELECTRICAL

- Constructed with durable materials to withstand harsh environments.
- Features a high-quality lens that ensures excellent light diffusion.
- Operates on a wide voltage range, making it suitable for various applications.
- Designed to operate efficiently in a wide range of temperatures.
- Equipped with reliable dimming capabilities for customizable lighting.
- Ensures a high-power factor for efficient energy use.
- Built to last with a projected lifetime of over 100,000 hours.
- Comes with a robust warranty for peace of mind and long-term reliability.

PERFORMANCE DATA

CRI

80+

CCT

3000K, 4000K, 5000K

Projected Lifetime

>196,000 Hours (L70)
>60,000 Hours (L90)

Dimming

0-10V Dimming Standard,
10% down to 100%

Operating Temperature

-20°C to 50°C Ambient

Warranty

5 year Standard
10 year Optional

ORDERING INFORMATION

VSW / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____

SERIES SIZE WATTAGE CCT VOLTAGE DRIVER FEATURES FINISH CONTROLS EMERG. BATT. WARRANTY

FIXTURE SERIES	
VSW	Classic Style Wrap
SIZE	
4	4 FT Nominal Length
WATTAGE*	
25WS	15 W, 20 W, 25 W Select. (2 FT)
35WS	25 W, 30 W, 35 W Select. (4 FT)
CCT	
CS	80+ CRI, 30K, 40K, 50K CCT Select.
VOLTAGE	
UNV	Universal 120-277VAC

DRIVER FEATURES	
10V	0-10 V Dimming
12A	12 V Aux Power & 0-10 V Dimming
FINISH	
WH	White Finish
CONTROLS	
MUSD	Motion Sensor, UltraSonic, Line Voltage, Direct Mount (Standard)
EMERGENCY BATT. BACKUP	
EM4	4 Watt 90 Min. Emerg. Batt.
WARRANTY	
-	5 Year Warranty (Standard)
10Y	10 Year Warranty

PERFORMANCE DATA

VSW 25WS 1 X 2							
SETTING	SYSTEM WATTS	3000K		4000K		5000K	
		LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)
LV1	15 W	2,190 lm	146 lm/W	2,250 lm	150 lm/W	2,220 lm	148 lm/W
LV2	20 W	2,920 lm	146 lm/W	3,000 lm	150 lm/W	2,960 lm	148 lm/W
LV3	25 W	3,650 lm	146 lm/W	3,750 lm	150 lm/W	3,700 lm	148 lm/W

VSW 35WS 1 X 4							
SETTING	SYSTEM WATTS	3000K		4000K		5000K	
		LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)
LV1	25 W	3,650 lm	146 lm/W	3,750 lm	150 lm/W	3,700 lm	148 lm/W
LV2	30 W	4,380 lm	146 lm/W	4,500 lm	150 lm/W	4,440 lm	148 lm/W
LV3	35 W	5,110 lm	146 lm/W	5,250 lm	150 lm/W	5,180 lm	148 lm/W

DIMENSIONS

unit: mm/inch

