



□□□□□	
□□□□□□	
□□□□□□	
□□□□	



FEATURES

- Casting thermally conducts LED heat to optimize performance and long life.
- With corrosion-resistant powder coating that provides protection and architectural appearance while adapting well to the environment.

CONSTRUCTION & ELECTRICAL

- Rugged Die Cast one piece aluminum housing.
- Low profile, 3G rated design reduces wind loading requirements.
- Universal 120-277VAC 50/60 Hz or 347-480VAC Input voltage options.
- Optional 0-10V Dimming (10%-100%)
- Optional Surge Protection
 - 10KV - (120-277VAC)
- Power Factor > 0.9
- THD < 20%

PERFORMANCE DATA

CRI / CCT

80+ CRI, 3000K, 4000K, 5000K

Projected Lifetime

>50,000 Hours (L70)

Dimming

10% down to 100%
0-10V Dimming Standard,

Operating Temperature

-40°C to +50°C Ambient

Warranty

5 year Standard
10 year Optional

ORDERING INFORMATION

ZARA / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____ / _____
SERIES WATTAGE CCT LENS DISTRIB. VOLTAGE DRIVER FEATURES FINISH CAGE & BAND TOP & FINIAL PHOTOCELL CONTROLS SHIELDING SURGE PROTECTION BUY AMERICA

FIXTURE SERIES	
ZARA	LED Acorn Post Top
WATTAGE	
15W	15 Watts
30W	30 Watts
55W	55 Watts
85W	85 Watts
100W	100 Watts
130W	130 Watts
155W	155 Watts
185W	180 Watts
CRI/CCT	
27	70+ CRI, 2700K
30	70+ CRI, 3000K
40	70+ CRI, 4000K
50	70+ CRI, 5000K
LENS	
PAL	Prismatic Acrylic Lens

DISTRIBUTION	
T3	Type III Forward Throw Distribution
T5	Type V Forward Throw Distribution
VOLTAGE	
UNV	Universal 120-277VAC
UHV	Universal High 347-480 VAC
DRIVER FEATURES	
10V	0-10V Dimming
ND	Non-Dimming
FINISH	
BL	Black Powder Coat Finish (Standard)
BZ	Bronze Powder Coat Finish (MOQ & ext. lead times may apply)
BLMG	Black Marine Grade Powder Coat Finish (MOQ & ext. lead times may apply)
BZMG	Bronze Marine Grade Powder Coat Finish (MOQ & ext. lead times may apply)
CAGE & BAND	
NDCB	No Decorative Cage or Band
CAFB	Cast Aluminum Cage w/ Flat Band

TOP & FINIAL	
CATF	Cast Aluminum Top and Finial
NTOF	No Top or Finial
PHOTOCELL	
PC	120-277 VAC Photocell
CONTROLS	
MWI	Cast Aluminum Top and Finial
MWI2L	Motion Sensor, Microwave Occ., Internal Mount Bi-Level
SHIELDING	
BLGS	Back Light Glare Shield
SURGE PROTECTION	
10KV	10,000 V Surge Protection
BUY AMERICA	
-	Standard Production and Assembly
BAA	Buy America Act Compliant
WARRANTY	
-	5 Year Warranty (Standard)
10Y	10 Year Warranty
10YL	10 Year Warranty with Labor



ZARA - PERFORMANCE TABLE						
SUSPECT WAYS	3000K 80lm		4000K 80lm		5000K 80lm	
	LUMENS	LPW	LUMENS	LPW	LUMENS	LPW
15W	1500	100	1575	105	1650	110
30W	3000	100	3150	105	3300	110
55W	5500	100	5775	105	6050	110
85W	8500	100	8925	105	9350	110
100W	10000	100	10500	105	11000	110
130W	13000	100	13650	105	14300	110
155W	15500	100	16125	105	17050	110
185W	18500	100	19275	105	20350	110

DIMENSIONS

