




Client:	
Order #:	
Project:	
Type:	



DESCRIPTION

The CYLARA LED cylinder downlight has wide array of versatile options that allow for easy matching to your interior project's aesthetic. With standard white and black finishes you can select from 4 different internal baffle colors, 7 Decorative Reflector colors letting these fixture stand out as an accent to the interior design or meld into the background based on the end user's preference. With both surface and suspension options, 3 Diameters, 3 selectable wattages, 8 CCT options, 4 optical distributions, 4 internal baffle colors, 7 decorative reflectors, and plenty of mounting options the possibilities are only limited by your imagination.

FEATURES

- Highly configurable with over 100,000 possible option combinations.
- CCT and CRI options to meet high end project requirements.
- Mounting options for surface mounting on both hard top and recessed jboxes.
- Suspension options including both cable and rigid stems in multiple lengths to match your projects requirements.
- 4 available optical distributions to put the light where you need it, and to allow greater flexibility for architectural lighting designers.

CONSTRUCTION & ELECTRICAL

- Modular Design with COB LED Chip
- Die cast Aluminum Housing for exceptional thermal management
- UV Stabilized White Powder Coat Finish
- RoHS Compliant with minimal Mercury.
- 0-10V, Dim to Off or 120V Triac Dimming
- Damp Location Rated
- Power Factor ≥ 0.9
- THD $< 20\%$

PERFORMANCE DATA

EFFICACY

90-105 Lumens per Watt (LPW)

CCT/CRI

30K, 40K or 50K, 70+ CRI

RATED LIFE

>91,000+ Hours (L80)
>153,000+ Hours (L70)

LUMEN OUTPUT

Lumen Output Ranges from
1,140 to 5,220 Lumens

OPERATING TEMPS

-40°C to 40°C Ambient

WARRANTY

5 year Standard
10 Year Extended
10 Year Extended with Labor

ORDERING INFORMATION

CYLARA

SERIES / SIZE / WATTAGE / CRI/CCT / OPTICAL DISTRIB. / VOLTAGE / DRIVER FEATURES / FINISH / BAFFLE COLOR / DEC. REF. COLOR / MOUNTING / SUSP. OPTIONS / WARRANTY

FIXTURE SERIES	
CYLARA	LED Cylinder Down Light
SIZE	
4	4 inch Nominal Diameter Cylinder
6	6 inch Nominal Diameter Cylinder
8	8 inch Nominal Diameter Cylinder
WATTAGE	
25WS	12W, 18W, 25W Select. (4 Inch)
40WS	20W, 30W, 40W Select. (6 Inch)
58WS	30W, 45W, 58W Select. (8 Inch)
CRI/CCT	
827	80+ CRI, 2700K CCT
830	80+ CRI, 3000K CCT
835	80+ CRI, 3500K CCT
840	80+ CRI, 4000K CCT
927	90+ CRI, 2700K CCT
930	90+ CRI, 3000K CCT
935	90+ CRI, 3500K CCT
940	90+ CRI, 4000K CCT

OPTICAL DISTRIBUTION	
NOD	Narrow 15° Optical Distribution
MOD	Medium 24° Optical Distribution
WOD	Wide 36° Optical Distribution
FOD	Flood 60° Optical Distribution
VOLTAGE	
UNV	Universal 120-277VAC
DRIVER FEATURES	
99D	0-10V Dimming - 100-1% (25WS, 40WS Only)
10V	0-10V Dimming
TRIAC	120V TRIAC Line Dimming (25WS, 40WS Only)
FINISH	
WH	White Finish
BL	Black Finish
BAFFLE COLOR	
WHB	White Baffle
BLB	Black Baffle
COPB	Copper Baffle
CHRB	Chrome Baffle

DECORATIVE REFLECTOR COLOR (Optional)	
BRF	Blue Decorative Reflector
YRF	Yellow Decorative Reflector (MOQ & Ext. Lead)
GRF	Green Decorative Reflector (MOQ & Ext. Lead)
TRF	Transparent Decorative Reflector (MOQ & Ext. Lead)
RRF	Red Decorative Reflector (MOQ & Ext. Lead)
SRFB	12 Inch Black Spun Reflector (4 Inch Only)
SRFW	12 Inch White Spun Reflector (4 Inch Only)
MOUNTING	
RJBP	Flat Canopy for Recessed Jbox (Suspended Options)
SJBP	Surface Mount Canopy J Box with Conduit Cutout
RJBS	Surface Mount for Recessed JBox
SUSPENSION OPTIONS	
CS2FT	2 FT Nominal Length Cable Suspension
CS4FT	4 FT Nominal Length Cable Suspension
CS8FT	8 FT Nominal Length Cable Suspension
RS2FT	2 FT Nominal Length Rigid Stem Suspension
RS4FT	4 FT Nominal Length Rigid Stem Suspension
RS8FT	8 FT Nominal Length Rigid Stem Suspension

MOUNTING OPTIONS

**SJBP - Surface Mount
Canopy J Box with
Conduit Cutout**



**RJBP - Flat Canopy for
Recessed J Box**



**RJBS -Surface Mount Canopy
for Recessed J Box**



LISTED
E504298
Suitable for
Damp Locations




**OVER 100,000 OPTIONS,
CONFIGURABLE IN SECONDS**

Whether you need pendants in a specific finish or surface mount in a certain trims, we have you covered. With our user-friendly ordering guide, you can try out every combination according to your space required.



DIMENSIONS



SURFACE



